

si d	Sinc _	670	910	1270	1630	1870	2230	2470	2710
SX	FRANK	610	850	1210	1570	1810	2170	2410	2650
099	009	AA0606	AA0609	AA0612	AA0616	AA0618	AA0622	AA0624	AA0627
920	860	AA0906	AA0909	AA0912	AA0916	AA0918	AA0922	AA0924	AA0927
1090	1030	AA1006	AA1009	AA1012	AA1016	AA1018	AA1022	AA1024	AA1027
1260	1200	AA1206	AA1209	AA1212	AA1216	AA1218	AA1222	AA1224	AA1227
1430	1370	AA1406	AA1409	AA1412	AA1416	AA1418	AA1422	AA1424	AA1427
1520	1460	AA1506	AA1509	AA1512	AA1516	AA1518	AA1522	AA1524	AA1527
1860	1800	AAT1806	AAT1809	AAT1812	AAT1816	AAT1818	AAT1822	AAT1824	1200 AAT1827
1860	1800	AA1806	AA1809	AATT1812	AATT1816	AATT1818	AATT1822	AATT1824	600 600 600 AATT1827
2110	2050	AAT2006	AAT2009	AAT2012	AAT2016	AAT2018	AAT2022	AAT2024	1370 680
2110	2050	AA2006	AA2009	AATT2012	AATT2016	AATT2018	AATT2022	AATT2024	680 690 680 AATT2027

Wideline's policy of continued improvement may result in changes of specification without notice. Windows and doors illustrated as viewed from outside.

- Configurations shown are reversible (ie. awning/fixed can be reversed to be fixed/awning).
- Single and double glazing available up to 20mm total thickness.
- Colonial, Montgomery and Endeavour bars are available for awning windows.
- Awning windows rate to a maximum BAL-40.
- Sash restrictors available to limit sash opening to 100mm.
- Stud opening size shown applies to frames fitted with reveals for brick veneer applications.



